Application No.: 10/517685

Case No.: 57894US004

Amendments to the Claims:

The following Listing of Claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1-37. (Canceled)

- 38. (Currently amended) A method for the manufacture of a shock indicator, comprising:
 - (A) providing a base comprising a first surface and a second surface, the second surface of the base associated with an attachment means; and
 - (B) placing an indicator in association with the first surface of the base, the indicator comprising an agglomerated powder comprising powder particles arranged (i) in a first configuration when the shock indicator is in a first state prior to a shock event, and (ii) in a second configuration when the shock indicator is in a second state following a shock event, wherein placing an indicator in association with the first surface of the base comprises depositing a slurry in association with the first surface and thereafter drying the slurry.
- 39. (Original) The method of claim 38 further comprising placing a containment member over the first side of the base and over the indicator, the containment member being transparent, thereby facilitating the visual determination of whether the indicator is in the first configuration or the second configuration.

40-42. (Canceled)

- 43. (Original) The method of claim 38, further comprising providing a means for attaching the indicator to another surface.
- 44. (Canceled)

Application No.: 10/517685

Case No.: 57894US004

- 45. (Previously presented) The method of claim 38 wherein placing an indicator in association with the first surface of the base further comprises placing a plurality of indicators in association with the first side of the base, each indicator comprising a plurality of powder particles arranged (i) in a first configuration prior to a shock event, and (ii) in a second configuration following a shock event.
- 46. (Original) The method of claim 38 further comprising associating an electronic device with the shock indicator, the device selected from the group consisting of cellular telephone, personal digital assistant, hand held computer and digital camera.

47-48. (Canceled)